

TCS40EA18 18" Rear Handle Chain Saw



**Includes:**

**Features:**

- 18" Oregon® Bar & Chain (Assembled)
- Bar & Chain Protective Cover
- Srench
- **39.6 cc 1.6 hp PureFire® two-stroke engine** meets emissions levels without sacrificing power, adding weight, or creating maintenance headaches
- **S-Start pull force reduction system and purge primer bulb** gives quick and easy starts
- **18" Oregon® sprocket nose bar and chain** reduces kickback and provides excellent cutting performance
- **Vibration dampening system** for user comfort and less fatigue
- **Outstanding power-to-weight** reduces fatigue resulting in higher productivity
- **Side access chain tensioner** provides for quick and easy chain adjustment
- **Inertia activated chain brake** immediately stops chain rotation for improved safety
- **Two bar mounting studs** keep the chain at peak cutting efficiency
- **Covered** by Tanaka's two-year commercial use warranty, seven-year consumer use warranty and one-year rental use warranty
- [Download the TCS40EA18 Hangtag](#)

Includes:

- 18" Oregon® Bar & Chain (Assembled)
- Bar & Chain Protective Cover
- Srench

Specifications

Engine Type	PureFire® Two-Stroke
Displacement	39.6 cc
Output	2.4 HP
Fuel Tank Capacity	12.8 Fl. Oz.
Carburetion	Walbro® Diaphragm w/ Purge Primer
Bar & Chain Brand	Oregon® Sprocket Nose
Opt.Bar&Chain Combinations	14", 16"
Pitch	.325" (low profile)
Chain Brake	Inertia Activated
Dry Weight	9.9 lbs (Powerhead Only)
EPA Phase 3 Compliant	Yes
CARB Tier III Compliant	Yes

Gas/Oil Ratio            50:1 (JASO FD Rated)  
Warranty                 2-Year Commercial Use, 7-Year Consumer Use,  
                                 1-Year Rental Use

---