UB18DJL 18V Lithium Ion LED Torch/Flash Light (Tool Body Only)



Includes:

Features:

- 18V Li-Ion Slide-Type Battery 3.0Ah (BSL1830) (330067)
- 18V Li-Ion Slide-Type Battery 31.5Ah (BSL1815X) (330139)
- 14.4V-18V Li-Ion Rapid Charger (UC18YRSL)
- **Covered by Hitachi's 5-year warranty**
- **Compatible with** Hitachi's 14.4V - 18V Lithium Ion slide-type batteries for fade free power, less weight and 3x the total battery life of traditional batteries (batteries and chargers sold separately)
- **247 degree adjustable head** on the left-right joint that can maneuver into 7 different positions
- **180 degree adjustable head** on the up-down joint that can maneuver into 5 different positions
- **Four brightness settings** for ultimate convenience and flexibility
- **Long 26 hour run time on torch light mode** (assuming 18V 3.0Ah battery) for efficient use on a charge
- **Delivers 10 to 31 hours of run time (**depending on the setting) on flashlight mode (assuming 18V 3.0Ah battery) for maximum lighting needs on a charge
- **Hook** allows for easy hanging from bars or beams on the jobsite to get light where needed
- **Convenient free standing design** from floor as needed
- **Lightweight at only 0.7 lbs** (without battery) for easy transport and storage
- Download the UB18DJL Tool Card

Optional:

- 18V Li-Ion Slide-Type Battery 3.0Ah (BSL1830) (330067)
- 18V Li-Ion Slide-Type Battery 31.5Ah (BSL1815X) (330139)
- 14.4V-18V Li-Ion Rapid Charger (UC18YRSL)

Specifications

Volts	**18**
Torch Light	**6,000 Lux**
Work Light- High	**110 Lux**
Work Light- Mid	**55 Lux**
Work Light- Low	**27 Lux**
Batteries Included	**0**

Batteries Included	**0**
Torch Light Run Time (3.0Ah)	**26 Hours**
Work Light Run Time(3.0Ah)	**High(10hr), Mid(18hr), Low(31hr)**
Torch Light Source	**LED (3W) x 1**
Work Light Source(High)	**LED (0.5W) x 12**
Work Light Source(Med)	**LED (0.5W) x 6**
Work Light Source(Low)	**LED (0.5W) x 3**
Left-Right Joint	**7-Position, 270 Degrees**
Up/Down Joint	**5-Position, 180 Degrees**
Warranty	**5-Year**
